

Industrial Sealer (IS)

The industrial sealer is an easy to operate, heavy duty sealer for packaging all kinds of products. The sealer is pneumatically operated and requires connection to a compressed air supply with 6 bar pressure. The sealing and cooling time are controlled by potentiometers and the machine is activated via a foot pedal. The Audion industrial sealers are available in different sizes to suit bag widths of up to 1300 mm.

The sealing bars are both heated and can be positioned vertically and horizontally with four positions in between, to suit the working position. All modern packaging materials can be used from polyethylene, polypropylene, PVC and all kinds of laminates. The machine is supplied on wheels for ease of manoeuvrability. The bag containing product is placed between the open sealing jaws. By pressing the

foot pedal the sealing bars will close and automatically activate the sealing cycle. After sealing, the sealing bars open and the sealed bag can be removed.



IS 750 vertical position



IS 750 horizontal position

Applications:				
Technical specifications	IS 475	IS 750	IS 1000	IS 1300
Seal length	475 mm	750 mm	1000 mm	1300 mm
Seal width	5 mm	5 mm	5 mm	5 mm
Film thickness	Max. 2x0,2 mm	Max. 2x0,2 mm	Max. 2x0,2 mm	Max. 2x0,2 mm
Voltage	230 V/50-60 Hz	230 V/50-60 Hz	230 V/50-60 Hz	230 V/50-60 Hz
Consumption	3300 W	3000 W	2400 W	1800 W
Dimensions of packed machine	70x57x140 cm	99x59x139 cm	124x59x139 cm	155x59x139 cm
Weight of machine	66 kg	74 kg	78 kg	80 kg

Options

Built-in compressor (ISC) if there is no air circuit available.
 Seal width of 8 mm (IS 750, 1000, 1300)

Accessories

Working table (OT VIS)