

CONTIMED® D666 MPC/MPCV

The D666 MPC/ MPCV are our advanced medical rotary sealers for sealing and coding medical sterilization pouches. These sealers are developed to seal pouches according to DIN 58953 Part 7 and are suitable for packing sterilized products according to ISO 11607 and EN 868. Using a multi-line seal, self correcting seal pressure and an in-feed speed of 10m/min., the D666 MPC/ MPCV can be used for closing paper/ polypropylene or Tyvec pouches. The built-in matrix printer can be used to print: date, operator name, serial number and codes, directly on the pouches according to the most recent tracking standards (EN 980 symbols). The D666MPC can be programmed through the keypad, but can also be connected to a PC/network to be programmed. The validatable version; D666 MPCV can be used for validatable processes through constant monitoring of all seal parameters and alarm / block functions when a parameter is out of range.

Features AUDION CONTIMED D666 MPC/MPCV

- Stainless steel (AISI 304) top cover plate (epoxy coated base)
- 4 lines LCD display for parameter settings / programming
- Energy saving standby function; machine starts through optical sensor
- Digital microprocessor controlled temperature setting / data input / storage
- Sealing temperature: 50°C - 210°C
- Automatic in-feed block when temperature changes more than +/- 5°C
- 15 mm seal width (multi line seal)
- Self adjusting pressure wheel adapts to different pouch thicknesses
- Fixed sealing speed: 10m / min
- Internal 9 dots matrix printer
- Printed symbols according to the EN980 standard
- Production date, different expiry periods, operator names, batch numbers, different counter functions programmable
- Possibility to save data settings
- Internal clock / calendar function
- Adjustable infeed guide
- CE certified
- Safety thermostat

Extra Features D666 MPCV

- Automatic in-feed block when speed changes more than +5% or -9% (only at MPCV version)
- Automatic in-feed block when pressure changes more than +2 kg or -1 kg (only at MPCV version)

Available Options

- Stainless steel support table
- Stainless steel slip roller conveyor
- Bar code scanner + PC software to enter parameter settings
- Label printer (can also print bar codes)

Machine Specifications

- Voltage: 230 V (+/-10%) - 1 Ph - 50/60 Hz (others upon request)
- Temperature controller accuracy +/- 1%
- Dimensions (lxwxh): 650x280x240 mm
- Weight: 23 kg



D666 MPCV + slip roller conveyor + label printer