

# D 552 AVTS BANDSEALER

---

## Stainless steel vertical bandsealer

The D 552 AVTS bandsealer is a stainless steel bandsealer with conveyor belt. Capable of sealing a wide range of bags such as stand-up pouches, gusseted bags, pillow-type bags, sachets, barriers bags, etc. This makes the D 552 AVTS a versatile band sealer which has proven itself in various sectors like the Food industry and Medical/Pharma/High-Tech.

Designed for large pre-made bags that are sealed standing up. Ideal for powder, liquid, or solid products that would spill if sealed lying flat. The sealing head of the Audion D 552 AVTS can be rotated 90°C, from vertical to horizontal. This unique feature makes the D 552 AVTS a two in one band sealer and makes it easier to carry out maintenance.

["D 552 AVTS a Vertical and Horizontal stainless steel bandsealer in one"](#)

The height of the machine and the conveyor belt can be adjusted to your packaging needs. The digital control panel makes the machine easy to use and minimize the operator training. The easy swing castors enables you to move the band sealer from one location to another. Plug and play and you can start the production again. The speed of this conveyor belt can be synchronized to the sealing unit from the control panel.

[If you have a bagging operation in which you wish to speed up production](#)

This robust stainless steel bandsealer is designed for heavy duty continuous bag sealing applications where versatility, power, speed, and durability are a must!

### Benefits

- Stainless steel – Industrial-grade machines
- Fast Warm-Up time
- Sealing head can be rotated 90 degrees
- Versatile band sealer
- Simple to Use – minimal operator training
- Height of the sealing head can be adjusted
- Height of the conveyor belt can be adjusted
- Portable – easy swing casters with lock
- Digital control panel
- Automatic cool down function
- Makes strong, professional-looking airtight seals
- High quality PTFE seal belts
- Conveyor belt speed can be adjusted / synchronized
- Extremely easy to use and maintain

### Options

- Extension of the axes with 65 mm up to 100mm (header cards)
- Extension of the frame with 300mm up to 1855mm
- Left right version epoxy model
- Left right version stainless steel model
- 20 mm wide seal
- Double heating elements

### Accessories

- Spare parts kit contains:
  - 2x v-belt 500mm
  - 2x v-belt 1500mm
  - 4x PTFE belt
  - 1x element

Markets

- Food
  - Pet-food
  - Medical
  - Fish
  - Pharma
  - High-Tech
  - Meat & Poultry industry
  - Food processing
  - Direct marketing
  - Non-food industry
  - Electronics
-

## SPECIFICATIONS

Producto	D 552 AVTS
Longitud de sellado	Unlimited
Anchura de sellado	10 mm
Tipo de máquina	Selladora continua, Semi-automático
Modelo	De Suelo
Envoltorio	Acero Inoxidable
Dimensions Machine	1464mm (L) x 607mm (W) x 1555mm (H)
Control de pedal	No
Tipo de film	Celofán, Film laminado, Bolsas preparadas, PP (polipropileno), PE (polietileno)
Grosor de film	2 X 200 micron (min 2 x 20)
Tipo de envase	Bolso
Sector/aplicación	Panadería, Café y té, Frutas y verduras, Componentes industriales, Artículos de oficina, Embalaje y logística, Cominda animales, Tienda minorista
Tipo de producto	Fluido, Granular, Polvo, Sólido
Sealing speed	Max. 10 meter per minute
Conveyor belt height	Min 475 mm / Max 975 mm
Voltage	230 V - 16 A
Frequency	50 - 60 Hz
Power	1100 W
Dimensions	1450 L x 607 W x 1555 H mm
Weight	120 kg

[Share this entry](#)