
ISMS I020

Audion Industrial Sealer Magneta: a compact and powerful tabletop sealer for heavy duty

This professional impulse sealer is suitable for sealing almost all modern film materials (PE/PP or laminates). Thick films can be sealed due to the bi-active 5 mm heating of the sealing bars. The ISM has been developed for heavy duty and intensive use. The sealing bars are closed by means of a light pressure on the electric foot operation after which the ISM will produce a powerful and strong 5 mm seal, driven by the electromotor.

The digital control panel easily allows you to set the ideal sealing and cooling time. Due to the special construction of sealwire tensioners the sealwire remains optimally tight even during intensive use. This ensures an excellent and reliable 5 mm seal.

The Industrial Sealer Magneta is available in epoxy and stainless steel version.

Optionally, a cutting device is available at the 620 and I020 models.

Benefits

- Bi-active 5 mm sealing bars which allow you to seal almost all modern film materials
- Industrial sealwire tensioners ensure an excellent seal performance
- Activation by electrical foot operation
- Seal bars are driven by electromotor
- Magnet-closure: sealing arm remains automatically closed during sealing and cooling
- User-friendly digital operation panel for programming sealing and cooling time
- No external air pressure required

Options / Accessories

Option:

- Knife option: for cutting the required bagsize out of tubular film and /or to cut away the spare film above the seal.

Accessories:

- Support: Allows the machine to be used with a vertical sealing position
- Bag support: Supports heavier and / or bigger bags while the operator has both hands available to guide the bag between the seal bars
- Film roll holder: For unwinding the film roll
- Polylock: Prevents the film from rolling back

Markets

- Food packaging (ISM is also available in stainless steel)
- Medical packaging
- Parts packaging

SPECIFICATIONS

Produit	I020 ISMS
Longueur de soudure	1020 mm
Largeur de soudure	5 mm
Type de machine	Soudeuse manuelles, Soudeuse par impulsion
Max. Film thickness	2 x 200 Micron
Dimensions	1107 x 384 x 202 mm
Machine weight (incl. pedal)	26,3 Kg
Voltage	230V - 1ph - 50/60Hz
Consumption	1100 W
Modèle	Sur Table
Revêtement	Acier Inox
Couteau	Yes, optional
Pédale de commande	Oui
Type de film	Film stratifiée, Sachets de conditionnement, PVC, PP (polypropylène), PE (polyéthylène)
Branche/Application	Boulangerie-pâtisserie, Café et thé, Service d'incendie, Fruits et légumes, Pièces industrielles, Fournitures de bureau, Emballage et logistique, Nourriture des animaux, Magasin de détail
Type d'emballage	Sac
Type de produit	Fluide, Granulé, Poudre, Solide