



The D 545 AV is Audion's most compact vertical band sealer. On this handy tabletop continuous sealer, ready-made-bags are sealed in a standing / vertical position.

The standing position is ideal for powders, liquids or solid products that would spill if sealed lying flat. The temperature, running speed and cooling (by means of a special fan) are all easily adjustable via an easy-to-use digital control panel.

The D 545 AV can be programmed with up to 9 pre-set seal settings for different packaging / bag sizes / materials. By using PTFE bands inside the machine, materials like polyethylene, polypropylene, cellophane, paper, aluminum and other laminates are sealed with a reliable 10 mm seal. It is also possible to seal header cards with the D 545 AV.

The integrated conveyor has a flow rate up to max 10 meters per minute (depending on the film thickness). The sealer is electrically adjustable in height with regard to the conveyor belt which enables you to seal bags with different heights and lengths, widths and thicknesses.

The sealing temperature is adjustable up to a maximum of 250 ° C.

Technical specifications

Model

D 545 AV

Type of machine

Continuous sealer, Semi-automatic

Operation

Easy-to-use digital control panel

Pre-set programs

Up to 9 pre-set programs can be entered

Covering

Epoxy

Conveyor belt length

670 mm (inc. input plate)

Conveyor belt width

112 mm

Max. weight on conveyor belt

5 kg

Seal length

Unlimited

Seal width

10 mm

Type of package

Readymade bags

Thickness of film

2 x 200 micron (max)

Thickness of film

2 x 25 micron (min)

Type of film

Cellophane, Laminate, Ready Made Bags, PP (Polypropylene), PE (Polyethylene)

Max bag length

430 mm (distance of machine in regards of conveyor electrically adjustable)

Min bag length

135 mm

Max bag flap length

(above the seal)

45 mm

Max temperature

250° C (digitally adjustable)

Machine weight

45 kg

Machine dimensions

673 x 355 x 502/802 mm (WxDxH)

Branche/Application

Backery, Coffee & Tea, Industrial Parts, Office Supplies, Packaging & Logistics, Pet Food, Shop

Type of product

Fluid, Granulate, Powder, Solid

IP value

IP20

Low Voltage directive, EMC directive, Standards

2006/42/CE, 2004/108/CE, EN-ISO 12100, EN-IEC 60204-1

