
I50 PT

Futura Portable sealers – Audion’s smallest heat sealers

Sealing device to be used as hand model or with foot control as table model. A double-sided heated device with a P.F.T.E. protection.

Suitable for sealing polyethylene and polypropylene. Because both sealing bars are heated, the I50 PT can seal thicker films.

- Sealing length 150 mm.
- Sealing width 2 mm.
- Both seal bars are continuously heated
- Equipped with 3-position switch
- Seal bars are covered with PTFE
- max. power 65 W/ 230 V.

The Futura Portable sealers are continuously heated and are supplied in four different versions, for sealing many different packaging films:

- **Futura Poly** (I50 P) equipped with 1 welding bar, for sealing thin films (P.E.).
- **Futura Poly Twin** (I50 PT) with 2 welding bars for sealing thicker films (P.E.).
- **Futura Cello** (I50 C) with 2 profiled beams for sealing cellophane, paper, aluminium and other laminated films.
- **Futura Barrier** (I50 B) with 2 flat beams for sealing cellophane, paper-, aluminium- and other laminated films.

Options

- Foot operation

Accessories

- Suspension bracket

SPECIFICATIONS

Product	I50PT
Seal length	150 mm
Seal width	2 mm
Type of machine	Heat sealer
Model	Tong
Covering	Plastic-PA-Nylon
Knife	No
Pedal operated	Yes/No
Type of film	Ready Made Bags, PE (Polyethylene)
Thickness of film	2 x 250 micron
Type of package	Bag
Branche/Application	Bakery, Coffee & Tea, Industrial Parts, Office Supplies, Packaging & Logistics, Pet Food, Shop
Type of product	Fluid, Granulate, Powder, Solid