
63I PS

Due to its portable character, this machine is particularly suitable for sealing all kinds of strange and difficult shaped products. The bi-active seal bars (both upper and lower seal bar are equipped with a resistance wire) allows the sealing of thick polyethylene up to 2 x 0,3 mm. Furthermore it will be possible to seal most of the laminate films, a simple test will tell you if the machine will be adequate for your film or not.

The machine needs to be connected to a transformer, where the seal time can be set accordingly to the film you are using. Once the jaws are closed the button is pressed and the seal will start, indicated by a control light. After the sealing time has passed (max. 1-3 sec.) the sealing will stop automatically and you can open the tongs.

Length power cord approx.: 5 m

SPECIFICATIONS

Product	63I PS
Seal length	630 mm
Seal width	3 mm
Type of machine	Impulse sealer
Model	Tong
Covering	Plastic-PA-Nylon
Dimensions	40 x 70 x 15 cm
Weight	2,1 kg
Pedal operated	No
Type of film	Ready Made Bags, PE (Polyethylene)
Thickness of film	2 x 300 micron
Type of package	Bag
Branche/Application	Bakery, Fruit & Vegetables, Industrial Parts, Office Supplies, Packaging & Logistics, Pet Food, Shop
Type of product	Fluid, Granulate, Powder, Solid

TECHNICAL SPECIFICATIONS	TRANSFORMER
Voltage	230V-lph-50/60 Hz
Consumption	Max. 1500 Watt
Weight	7 Kg
Dimensions	270 x 190 x 190 mm

