

AUDIONVAC VM 243

Double chamber floor model

- Digital control panel with 10 programs
- Aluminum chamber
- Aluminum lid with window

This machine can also be supplied as validated version

Standard functions


- Vacuum (timer control)
- Seal
- Soft-air

- Multi cycles
- Gas plus function
- Expansion reduction

- Sensor control
- Bag cut-off seal
- 10 mm single seal
- 5 mm bi-active seal
- Seal I-2
- Gas flush (3 gas pipes on each bar)
- Gas kit
- Tilted plate for liquid containing bags
- ESD configuration

- 230 V – 1 Ph – 50 Hz
 - 200 V – 3 Ph – 50/60 Hz
 - 220 V – 1 Ph – 60 Hz
 - 208/230 V – 3 Ph – 60 Hz
 - 220/380 V – 3 Ph – 60 Hz
-

SPECIFICATIONS

Product	Audionvac VM 243
Seal length	440 mm
Seal width	3,5 mm double seal
Position of the sealing bar	 <i>long/long</i>
Effective chamber size (LxWxH)	(2x) 440 x 580 x 235 mm
Type of machine	Vacuum chamber
Model	Floor, Double Chamber
Covering	Stainless steel machine / Aluminum chamber
Pump capacity	63 m3/h
Pedal operated	No
Type of film	PA/PE, Vacuum Bags
Thickness of film	2 x 150 micron
Type of package	Bag
Branche/Application	Coffee & Tea, Fruit & Vegetables, Industrial Parts, Office Supplies, Packaging & Logistics, Shop
Type of product	Granulate, Powder, Solid