

---

# AUDIONVAC VMS 263

---

The hygienic construction ensures reliability in operation and low maintenance costs. This double chamber model has an effective vacuum chamber has a size of 2x 610x500x240. Richly equipped as standard with soft-air, IO program memory, time control. All together a rock solid machine which gives you benefits for years.

This machine can also be supplied as validated version.

### Benefits

- Standard time control
- Standard soft air to vacuum seal sharp products
- Busch vacuum pump
- Standard double seal
- Maintenance friendly and easy to clean construction
- Made from high quality materials
- Standard 2 seal bars front and back which doubles your packing capacity
- Standard with IO program memory Standard digital control panel with IO program memory
- Easy to operate with digital display
- Stainless steel chamber
- Standard equipped with 400-3-50 power supply

### Accessories

- Liquid control, for vacuum sealing liquids
- Advanced control system (ACS)
- Additional platform
- Extra cassette
- Filling plates for lid
- External vacuum adapter
- Spare part set
- Trolley

### Options

- Gas flush, modifies atmosphere packaging (MAP)
- Wide seal 10 mm
- Bi-active seal, is recommend to use when vacuum sealing aluminum or thicker bags.
- Inclined plate for 4 silicone holders
- Aluminum end blocks, for heavy duty packaging. Ensure an efficient and durable vacuum packaging process under the most extreme conditions.
- Aluminum end blocks for bi-active, for heavy duty packaging. Ensure an efficient and durable vacuum packaging process under the most extreme conditions.

- Validatable
- Calibration
- Cut-off seal, to easily tear off the residual plastic.
- I-2 cut-off seal, same as cut-off seal but in addition with I-2 cut-off seal the time and settings of the seal and cutting wire can be managed separately.
- Easy swing, enables the operator to easily move/swing the lid from one side to the other side of the vacuum packaging machine.
- Sensor control, constant, guaranteed end vacuum
- Power supply: 200-3-50/60 / 220-3-60

#### Markets

- Electronics
- Meat & Poultry industry
- Food processing
- Direct marketing
- Non-food industry

## SPECIFICATIONS

Product	Audionvac VMS 263
Seal length	610 mm
Seal width	3,5 mm double seal
Position of the sealing bar	
Effective chamber size (LxWxH)	(2x) 610 x 500 x 240
Type of machine	Validatable/calibratable/medical, Vacuum chamber, Double chamber, Medical
Model	Floor, Double Chamber
Covering	Stainless Steel
Pump capacity	100 m <sup>3</sup> /h
Pedal operated	No
Type of film	PA/PE, Vacuum Bags
Thickness of film	2 x 150 micron
Type of package	Bag
Branche/Application	Backery, Cheese, Coffee & Tea, Fish, Food, Fruit & Vegetables, Industrial Parts, Meat & Poultry, Medical & Laboratory, Office Supplies, Packaging & Logistics, Pet Food, Shop, Warehouse, Food Industry, Pharmaceutical Industry, Medical Industry, Seed Industry, Dental Industry, Laboratories
Type of product	Granulate, Powder, Solid