

AUDIONVAC VMS 903

Double chamber floor model with automatic lid and conveyor belts

- Digital control panel with 20 programs
- Stainless steel flat working plate
- Stainless steel lid
- Conveyor belts with quick-release attachment for cleaning
- Adjustable belt height

Standard functions

- Vacuum (timer control)
- Seal
- Soft-air

- Bag cut-off seal
- 8 mm seal
- Sensor pressure control (set percentage of pressure for vacuum and detect boiling point of product)
- External transport conveyor
- External pump
- Seal I-2 for 2 sealing bars
- 200V-3ph-50/60Hz
- 208/230V-3ph-60Hz
- 220/380V-3ph-60Hz

- Sensor control
- Bag cut-off seal

- 10 mm single seal
 - 5 mm bi-active seal
 - Seal I-2
 - Gas flush (4 gas pipes on each bar)
 - Gas kit
 - Tilted plate for liquid containing bags
 - Filling plates for lid
 - Easy swing
 - External pump
 - 230 V – 1 Ph – 50 Hz
 - 200 V – 3 Ph – 50/60 Hz
 - 220 V – 1 Ph – 60 Hz
 - 208/230 V – 3 Ph – 60 Hz
 - 220/380 V – 3 Ph – 60 Hz
-

SPECIFICATIONS

Product	Audionvac VMS 903
Seal length	840 mm
Seal width	3,5 mm double seal
Type of machine	Vacuum chamber
Model	Floor, Double Chamber
Covering	Stainless Steel
Pedal operated	No
Type of film	PA/PE, Vacuum Bags
Thickness of film	2 x 150 micron
Type of package	Bag
Branche/Application	Bakery, Cheese, Coffee & Tea, Fruit & Vegetables, Industrial Parts, Meat & Poultry, Office Supplies, Packaging & Logistics, Pet Food, Shop, Warehouse, Food Industry
Type of product	Granulate, Powder, Solid