

---

# H 20 SEAL/SHRINK COMBINATION

---

The seal/shrink combinations H20 and H25 are ideal for moderate production quantities (up to 300 packs per hour). The machines operate with a shrink hood.

The hood is closed by an electronic hold-down magnet during the film sealing and heat-shrink wrapping operations. Almost any product can be shrink wrapped in this clever machine. These AUDIONPACK machines have -due to an accurate temperature control - a better seal quality and longer wire lifetime as most other similar machines in this market segment.

---

Standard features

- Sealing and shrinking in one operation
- Electro-magnet closure of shrink hood
- Automatic shrink hood opening after completion of cycle
- Seal temperature controlled by microprocessor
- Shrink time and temperature controlled by microprocessor
- Multi languages LCD, parameters in text
- Memory capacity: 6 programs
- Possibility to adjust shrink delay
- Possibility to adjust hood opening delay
- Program options: seal only/ seal and shrink
- PTFE coated sealbar
- Rack in shrink chamber adjustable in height
- Movable Work shelf, free from reel holder
- Easy maintenance access
- CE Certified

## SPECIFICATIONS

Product	H 20
Seal length	440 mm
Seal width	0,7 mm
Type of machine	Shrink sealer
Model	Floor
Covering	Epoxy
Pedal operated	No
Type of film	PVC, PO (Polyolefin)
Thickness of film	2 x 30 micron
Type of package	Shrink Package
Branche/Application	Bakery, Cheese, Fruit & Vegetables, Industrial Parts, Office Supplies, Packaging & Logistics, Pet Food
Type of product	Solid
Max. weight of the products which can be packed	min: 50 gram max: 15 kg
Max. size of the products which can be packed	410 L x 250 W x 210 H mm
Machine weight	71 kg
Machine dimensions	1050 x 682 x 1015 mm