

AUDIONVAC VMS 333

Industrial single chamber with flat plate

The VMS 333 is a large single chamber vacuum packaging machine with flat plate of the Audionvac range. With the 5 different seal bar configuration and a total sealing length of 790 mm it can't go wrong.

This strong industrial floor model vacuum packaging machine is available as a basic industrial model and as a full option vacuum packaging machine. Made from heavy industrial materials which makes it a robust and durable packaging machine.

“Audionvac; professional range of vacuum packaging machines”

Richly equipped as standard with soft-air, I0 program memory, time control. All together a rock solid machine which gives you benefits for years.

This machine can also be supplied as validated version.

Please click here for:

- [General information about vacuum packing](#)
- [Difference between vacuum sealer and a vacuum chamber](#)

Benefits

- Standard time control
- Standard soft air to vacuum seal sharp products
- Busch vacuum pump
- Standard double seal
- Maintenance friendly and easy to clean construction
- Made from high quality materials
- Standard with 10 program memory Standard digital control panel with 10 program memory
- Easy to operate with digital display
- Stainless steel chamber
- Standard equipped with 400-3-50 power supply

Options

- 2 seal bars left right which doubles your packing capacity
- 2 seal bars front back which doubles your packing capacity
- 2 seal bars front right which doubles your packing capacity
- 3 seal bars left front right
- Gas flush, modifies atmosphere packaging (MAP)
- Wide seal 10 mm
- Bi-active seal, is recommend to use when vacuum sealing aluminum or thicker bags.
- Inclined plate for 2 silicone holders
- Inclined plate for 3 silicone holders
- Aluminum end blocks, for heavy duty packaging. Ensure an efficient and durable vacuum packaging process under the most extreme conditions.
- Aluminum end blocks for bi-active, for heavy duty packaging. Ensure an efficient and durable vacuum packaging process under the most extreme conditions.
- Validatable
- Calibration
- External pump
- Cut-off seal, to easily tear off the residual plastic.
- I-2 cut-off seal, same as cut-off seal but in addition with I-2 cut-off seal the time and settings of the seal and cutting wire can be managed separately.


- Sensor control, constant, guaranteed end vacuum
- Power supply: 200-3-50/60 / 220-3-60
- Adaptation for external exhaust (on request)

Accessories

Markets

- Electronics
 - Meat & Poultry industry
 - Food processing
 - Direct marketing
 - Non-food industry
-

SPECIFICATIONS

Product	Audionvac VMS 333
Seal length	790 mm
Seal width	3,5 mm double seal
Position of the sealing bar	
Effective chamber size (LxWxH)	790 x 460 x 200 mm / 710 x 550 x 200 mm / 790 x 490 x 200 mm
Type of machine	Validatable/calibratable/medical, Vacuum chamber
Model	Floor
Covering	Stainless Steel
Pump capacity	100 m ³ /h Busch pump
Pedal operated	No
Type of film	PA/PE, Vacuum Bags
Thickness of film	2 x 150 micron
Type of package	Bag
Branche/Application	Bakery, Cheese, Coffee & Tea, Fish, Food, Fruit & Vegetables, Industrial Parts, Meat & Poultry, Medical & Laboratory, Office Supplies, Packaging & Logistics, Pet Food, Shop, Warehouse, Food Industry, Pharmaceutical Industry, Medical Industry, Seed Industry, Dental Industry, Laboratories
Type of product	Granulate, Powder, Solid
Machine cycle	15 – 40 sec
Power	3,0 – 5,0 kW

Voltage	400V-3-50Hz
Weight	241 kg
Machine dimensions	790 x 900 x 1100 mm

[Share this entry](#)