

L 500SA

This semi automatic L-sealers can be used to pack your products in a safe, presentable way. Easy adjustment/settings of these sealers guarantee flexibility and a high production quantity. L-sealers can also be used in combination with our separate shrink tunnels.

Standard features

- Automatic cycle mode
- Scrap film winder
- Scrap film guide device
- PTFE-coated sealing blade
- Liquid cooling circuit
- Control glass for cooling liquid level
- Working height sealer and tunnel adjustable
- Emergency button
- Automatic transfer of the product to the shrink tunnel
- Adjustable shrink delay time for sealing thin films
- User-friendly control panel with LCD allowing:

-Machine information

-Counter

-Sealing temperature settings

-Conveyor speed

-Automatic cycle mode setting

-6 operating programs

-Failure codes indication

SPECIFICATIONS

Seal length	560 mm
Seal width	0,7 mm
Type of machine	Shrink sealer
Model	Floor
Covering	Epoxy
Knife	Option
Pedal operated	No
Type of film	PVC, PO (Polyolefin), PE (Polyethylene)
Thickness of film	2 x 50 micron
Type of package	Bag
Branche/Application	Bakery, Cheese, Fruit & Vegetables, Industrial Parts, Office Supplies, Packaging & Logistics, Pet Food, warehouse
Type of product	Solid