

TM I8

TE-Matic shrink tunnel which can be used in combination with L-Sealers and EL-Matic machines.

The main features of the TE-MATIC tunnel are:

- Adjustable shrink tunnel temperature
 - Adjustable conveyor speed
 - Tunnel air flow regulation by flaps
 - Tunnel conveyor with silicone coated rotating rollers
 - Control panel with back lighted LCD
 - Automatic cool down function for end of shift
 - Reduced power consumption
 - Rollers can be fixed for PE
 - 6 working programs
-

SPECIFICATIONS

Product	TM 18
Max. product height*	230 mm
Max. product width*	400 mm
Type of machine	Shrink tunnel
Model	Floor
Covering	Epoxy
Conveyor speed	Adjustable from 2,8 – 9,4 m/min
Tunnel temperature	85 – 200°C
Machine size	1310 x 832 x 1440 mm
Machine weight	187 kg
Voltage	380-415V-3PH+N+PE-50/60Hz
Power	8000W
Type of film	PVC, PO (Polyolefin), PE (Polyethylene)
Thickness of film	2 x 50 micron
Type of package	Shrink Package
Branche/Application	Bakery, Cheese, Fruit & Vegetables, Industrial Parts, Office Supplies, Packaging & Logistics, Pet Food
Type of product	Solid
The maximum product width and height can not be reached at the same time	